

Sugarcane Bagasse

REFERENCE MATERIAL

Pedigree

Institution: Alama Sugar Plantation Sample Preparation: Processed Bagasse

Location: Pointe Coupee County, LA Received at INL: 2015

Crop Year: 2014

Proximate, Ultimate & Calorimetry

Table 2. Proximate, ultimate, and calorific values for Reference Sugarcane Bagasse (reported on a dry basis)

Proximate ^a			Ultimate ^b						Calorimetry ^c	
%Volatile	%Ash	%Fixed Carbon	WHydrogen %Ca		%Nitrogen	%Oxygen	%Sulfur	HHV	LHV	
76.02	10.56	13.41	5.38	45.24	0.36	38.41	0.05	7828.73	6498.83	

^aProximate analysis was done according to ASTM D 5142-09

Elemental Ash

Table 3. Elemental ash composition^a of Reference Sugarcane Bagasse

%Al as Al₂O₃	%Ca as CaO	%Fe as Fe₂O₃	%K as K₂O		%Mn as MnO			%Si as SiO₂	%Ti as TiO₂	%S as SO₃
7.20	2.74	2.40	4.46	1.30	0.06	1.30	0.95	79.19	0.40	0.57

^aDetermined as described in ASTM standards D3174, D3682 and D6349

Contact

For questions regarding biomass material or analytical data please contact Amber Hoover at amber.hoover@inl.gov or 208-526-5992.

Visit the Bioenergy Feedstock Library (https://bioenergylibrary.inl.gov) for more information on biomass feedstocks.

^bUltimate analysis was conducted using a modified ASTM D5373-10 method (Flour and Plant Tissue Method) that uses a slightly different burn profile. Elemental sulfur content was determined using ASTM D4239-10, and oxygen content was determined by difference

^cHeating values (HHV, LHV) were determined with a calorimeter using ASTM D5865-10